



### FT 038.1010

cable winder from synthetic material, isolated, ball beared axle, cable locking device can be deactivated, with flat slip rings 10 poles and 10m cable Ölflex 10x1,5mm<sup>2</sup>, in series with wall bracket, ceiling bracket against extra charge

| Order-No.  | Weight               |
|------------|----------------------|
| 620 10 010 | 13.70 kg<br>30.20 lb |

#### Measures in mm/inch

|                       |                      |                      |
|-----------------------|----------------------|----------------------|
| <b>A:</b> 380 / 14,96 | <b>G:</b> 230 / 9,06 | <b>L:</b> 180 / 7,09 |
| <b>B:</b> 267 / 10,51 | <b>H:</b> 64 / 2,52  | <b>N:</b> 25 / 0,98  |
| <b>C:</b> 480 / 18,9  | <b>J:</b> 240 / 9,45 |                      |
| <b>D:</b> 80 / 3,15   | <b>K:</b> 131 /      |                      |
| <b>E:</b> 20 / 0,79   |                      |                      |
| <b>F:</b> 258 / 10,16 |                      |                      |



**Schill GmbH & Co. KG**  
Bruckstr. 44  
70734 Fellbach/Germany

Phone: +49 (0) 711 57 88 07-0  
Fax: +49 (0) 711 57 88 07-44  
info@schill.de  
www.schill.de